

Compress

ODU Split 2

8738206018

The information provided fulfills the requirements of regulations (EU) 811/2013 and (EU) 813/2013.

Productdata	Symbol	Unit	8738206018
Energy Efficiency Class			A+
Rated heat output (average climate conditions)	Prated	kW	3
Seasonal space heating energy efficiency (average climate conditions)	η_s	%	121
Annual energy consumption (average climate conditions)	Q_{HE}	kWh	1806
Annual energy consumption	Q_{HE}	GJ	-
Sound power level, indoors	L_{WA}	dB	36
Special precautions to be taken during assembly, installation or maintenance (if applicable)	see product accompanying documents		
Rated heat output (colder climate conditions)	Prated	kW	5
Rated heat output (warmer climate conditions)	Prated	kW	3
Seasonal space heating energy efficiency (colder climate conditions)	η_s	%	108
Seasonal space heating energy efficiency (warmer climate conditions)	η_s	%	133
Annual energy consumption (colder climate conditions)	Q_{HE}	kWh	4430
Annual energy consumption (colder climate)	Q_{HE}	GJ	-
Annual energy consumption (warmer climate conditions)	Q_{HE}	kWh	1181
Annual energy consumption (warmer climate)	Q_{HE}	GJ	-
Sound power level, outdoors	L_{WA}	dB	64
Air-to-water heat pump			Yes
Water-to-water heat pump			No
Brine-to-water heat pump			No
Low temperature heat pump			No
Equipped with a supplementary heater?			No
Heat pump combination heater			No
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C (average climate conditions)	Pdh	kW	2,4
Tj = + 2 °C (average climate conditions)	Pdh	kW	1,5
Tj = + 7 °C (average climate conditions)	Pdh	kW	1,5
Tj = + 12 °C (average climate conditions)	Pdh	kW	1,5
Tj = bivalent temperature (average climate conditions)	Pdh	kW	2,7
Tj = operation limit temperature	Pdh	kW	2,5
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	kW	2,5
Bivalent temperature (average climate conditions)	T_{biv}	°C	-10
Cycling interval capacity for heating (average climate conditions)	Pcych	kW	-
Degradation coefficient			-
Degradation co-efficient (average climate conditions)	Cdh		0,9
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj /			
Tj = - 7 °C (average climate conditions)	COPd		2,01
Tj = - 7 °C (average climate conditions)	PERd	%	-
Tj = + 2 °C (average climate conditions)	COPd		3,00
Tj = + 2 °C (average climate conditions)	PERd	%	-
Tj = + 7 °C (average climate conditions)	COPd		4,72
Tj = + 7 °C (average climate conditions)	PERd	%	-
Tj = + 12 °C (average climate conditions)	COPd		5,03
Tj = + 12 °C (average climate conditions)	PERd	%	-

Compress

ODU Split 2

8738206018

Productdata	Symbol	Unit	8738206018
Tj = bivalent temperature (average climate conditions)	COPd		1,80
Tj = bivalent temperature	PERd	%	-
Tj = operation limit temperature	COPd		1,72
Tj = operation limit temperature	PERd	%	-
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd		1,72
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	PERd	%	-
For air-to-water heat pumps: Operation limit temperature	TOL	°C	-15
Cycling interval efficiency (average climate conditions)	COP _{cy}		-
Cycling interval efficiency	PER _{cy}	%	-
Heating water operating limit temperature	WTOL	°C	57
Power consumption in modes other than active mode			
Off mode	P _{OFF}	kW	0,011
Thermostat-off mode	P _{TO}	kW	0,051
In standby mode	P _{SB}	kW	0,011
Crankcase heater mode	P _{CK}	kW	0,100
Supplementary heater			
Rated heat output supplementary heater	P _{sup}	kW	0,0
Type of energy input			Electric
Other items			
Capacity control			variable
Emissions of nitrogen oxides (only gas- or oil fired)	NO _x	mg/kWh	-
For air-to-water heat pumps: Rated air flow rate, outdoors		m ³ /h	1920
For brine-to-water heat pumps: Rated brine flow rate, outdoor heat exchanger		m ³ /h	-

Specific precautions for installation, maintenance as well as recycling and/or disposal are provided within the installation and operating manuals. Read and follow the installation and operating manuals.