

**Compress**

ODU Split 11t

8738206025

To the extent applicable to the product, the following data are based on the requirements of Regulations (EU) 811/2013 and (EU) 813/2013.

Productdata	Symbol	Unit	8738206025
Energy Efficiency Class			A++
Energy efficiency class (low temperature application)			A+++
Rated heat output (average climate conditions)	Prated	kW	9
Rated heat output (low temperature application, average climate conditions)	Prated	kW	12
Seasonal space heating energy efficiency (average climate conditions)	$\eta_s$	%	127
Seasonal space heating energy efficiency (low temperature application, average climate conditions)	$\eta_s$	%	183
Annual energy consumption (average climate conditions)	$Q_{HE}$	kWh	5748
Annual energy consumption (low temperature application, average climate conditions)	$Q_{HE}$	kWh	5204
Annual energy consumption	$Q_{HE}$	GJ	-
Sound power level, indoors	$L_{WA}$	dB	41
Special precautions to be taken during assembly, installation or maintenance (if applicable): see product accompanying documents			
Rated heat output (colder climate conditions)	Prated	kW	10
Rated heat output (low temperature application, colder climate conditions)	Prated	kW	11
Rated heat output (warmer climate conditions)	Prated	kW	10
Rated heat output (low temperature application, warmer climate conditions)	Prated	kW	12
Seasonal space heating energy efficiency (colder climate conditions)	$\eta_s$	%	112
Seasonal space heating energy efficiency (low temperature application, colder climate conditions)	$\eta_s$	%	146
Seasonal space heating energy efficiency (warmer climate conditions)	$\eta_s$	%	156
Seasonal space heating energy efficiency (low temperature application, warmer climate conditions)	$\eta_s$	%	217
Annual energy consumption (colder climate conditions)	$Q_{HE}$	kWh	8637
Annual energy consumption (colder climate)	$Q_{HE}$	GJ	-
Annual energy consumption (warmer climate conditions)	$Q_{HE}$	kWh	3525
Annual energy consumption (low temperature application, colder climate conditions)	$Q_{HE}$	kWh	7546
Annual energy consumption (warmer climate)	$Q_{HE}$	GJ	-
Annual energy consumption (low temperature application, warmer climate conditions)	$Q_{HE}$	kWh	2883
Sound power level, outdoors	$L_{WA}$	dB	67
Air-to-water heat pump			Yes
Water-to-water heat pump			No
Brine-to-water heat pump			No
Low temperature heat pump			No
Equipped with a supplementary heater?			Yes
Heat pump combination heater			No
<b>Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj</b>			
Tj = - 7 °C (average climate conditions)	Pdh	kW	8,0
Tj = + 2 °C (average climate conditions)	Pdh	kW	5,0
Tj = + 7 °C (average climate conditions)	Pdh	kW	6,2
Tj = + 12 °C (average climate conditions)	Pdh	kW	7,6
Tj = bivalent temperature (average climate conditions)	Pdh	kW	9,0
Tj = operation limit temperature	Pdh	kW	9,0
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	kW	9,0
Bivalent temperature (average climate conditions)	$T_{biv}$	°C	-10
Cycling interval capacity for heating (average climate conditions)	Pcych	kW	-
Degradation coefficient			-

Data at the time of printing. Latest version available on the Internet.

**Compress**

ODU Split 11t

8738206025

Productdata	Symbol	Unit	8738206025
Degradation co-efficient (average climate conditions)	Cdh		1,0
<b>Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj/</b>			
Tj = - 7 °C (average climate conditions)	COPd		2,04
Tj = - 7 °C (average climate conditions)	PERd	%	-
Tj = + 2 °C (average climate conditions)	COPd		3,21
Tj = + 2 °C (average climate conditions)	PERd	%	-
Tj = + 7 °C (average climate conditions)	COPd		4,08
Tj = + 7 °C (average climate conditions)	PERd	%	-
Tj = + 12 °C (average climate conditions)	COPd		5,77
Tj = + 12 °C (average climate conditions)	PERd	%	-
Tj = bivalent temperature (average climate conditions)	COPd		1,62
Tj = bivalent temperature	PERd	%	-
Tj = operation limit temperature	COPd		1,87
Tj = operation limit temperature	PERd	%	-
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd		1,87
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	PERd	%	-
For air-to-water heat pumps: Operation limit temperature	TOL	°C	-15
Cycling interval efficiency (average climate conditions)	COPcyc		-
Cycling interval efficiency	PERcyc	%	-
Heating water operating limit temperature	WTOL	°C	57
<b>Power consumption in modes other than active mode</b>			
Off mode	P <sub>OFF</sub>	kW	0,026
Thermostat-off mode	P <sub>TO</sub>	kW	0,000
In standby mode	P <sub>SB</sub>	kW	0,026
Crankcase heater mode	P <sub>CK</sub>	kW	0,053
<b>Supplementary heater</b>			
Rated heat output supplementary heater	P <sub>sup</sub>	kW	0,0
Type of energy input			Electric
<b>Other items</b>			
Capacity control			variable
Emissions of nitrogen oxides (only gas- or oil fired)	NO <sub>x</sub>	mg/kWh	-
For air-to-water heat pumps: Rated air flow rate, outdoors		m <sup>3</sup> /h	7200
For brine-to-water heat pumps: Rated brine flow rate, outdoor heat exchanger		m <sup>3</sup> /h	-

Further important information for installation, maintenance as well as recycling and/or disposal are provided within the installation and operating manuals. Read and follow the installation and operating manuals.