

Compress

ODU Split 13t

8738206026

To the extent applicable to the product, the following data are based on the requirements of Regulations (EU) 811/2013 and (EU) 813/2013.

Productdata	Symbol	Unit	8738206026
Energy Efficiency Class			A++
Energy efficiency class (low temperature application)			A++
Rated heat output (average climate conditions)	Prated	kW	11
Rated heat output (low temperature application, average climate conditions)	Prated	kW	12
Seasonal space heating energy efficiency (average climate conditions)	η_s	%	130
Seasonal space heating energy efficiency (low temperature application, average climate conditions)	η_s	%	168
Annual energy consumption (average climate conditions)	Q_{HE}	kWh	7043
Annual energy consumption (low temperature application, average climate conditions)	Q_{HE}	kWh	5965
Annual energy consumption	Q_{HE}	GJ	-
Sound power level, indoors	L_{WA}	dB	41
Special precautions to be taken during assembly, installation or maintenance (if applicable): see product accompanying documents			
Rated heat output (colder climate conditions)	Prated	kW	12
Rated heat output (low temperature application, colder climate conditions)	Prated	kW	14
Rated heat output (warmer climate conditions)	Prated	kW	11
Rated heat output (low temperature application, warmer climate conditions)	Prated	kW	13
Seasonal space heating energy efficiency (colder climate conditions)	η_s	%	111
Seasonal space heating energy efficiency (low temperature application, colder climate conditions)	η_s	%	144
Seasonal space heating energy efficiency (warmer climate conditions)	η_s	%	155
Seasonal space heating energy efficiency (low temperature application, warmer climate conditions)	η_s	%	211
Annual energy consumption (colder climate conditions)	Q_{HE}	kWh	10664
Annual energy consumption (colder climate)	Q_{HE}	GJ	-
Annual energy consumption (warmer climate conditions)	Q_{HE}	kWh	3774
Annual energy consumption (low temperature application, colder climate conditions)	Q_{HE}	kWh	9331
Annual energy consumption (warmer climate)	Q_{HE}	GJ	-
Annual energy consumption (low temperature application, warmer climate conditions)	Q_{HE}	kWh	3167
Sound power level, outdoors	L_{WA}	dB	67
Air-to-water heat pump			Yes
Water-to-water heat pump			No
Brine-to-water heat pump			No
Low temperature heat pump			No
Equipped with a supplementary heater?			Yes
Heat pump combination heater			No
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature Tj			
Tj = - 7 °C (average climate conditions)	Pdh	kW	10,0
Tj = + 2 °C (average climate conditions)	Pdh	kW	6,1
Tj = + 7 °C (average climate conditions)	Pdh	kW	6,4
Tj = + 12 °C (average climate conditions)	Pdh	kW	7,3
Tj = bivalent temperature (average climate conditions)	Pdh	kW	11,3
Tj = operation limit temperature	Pdh	kW	10,1
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	Pdh	kW	10,1
Bivalent temperature (average climate conditions)	T_{biv}	°C	-10
Cycling interval capacity for heating (average climate conditions)	Pcych	kW	-
Degradation coefficient			-

Data at the time of printing. Latest version available on the Internet.

Compress

ODU Split 13t

8738206026

Productdata	Symbol	Unit	8738206026
Degradation co-efficient (average climate conditions)	Cdh		1,0
Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature Tj/			
Tj = - 7 °C (average climate conditions)	COPd		2,03
Tj = - 7 °C (average climate conditions)	PERd	%	-
Tj = + 2 °C (average climate conditions)	COPd		3,31
Tj = + 2 °C (average climate conditions)	PERd	%	-
Tj = + 7 °C (average climate conditions)	COPd		4,29
Tj = + 7 °C (average climate conditions)	PERd	%	-
Tj = + 12 °C (average climate conditions)	COPd		5,09
Tj = + 12 °C (average climate conditions)	PERd	%	-
Tj = bivalent temperature (average climate conditions)	COPd		1,81
Tj = bivalent temperature	PERd	%	-
Tj = operation limit temperature	COPd		1,96
Tj = operation limit temperature	PERd	%	-
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	COPd		1,96
For air-to-water heat pumps: Tj = - 15 °C (if TOL < - 20 °C)	PERd	%	-
For air-to-water heat pumps: Operation limit temperature	TOL	°C	-15
Cycling interval efficiency (average climate conditions)	COPcyc		-
Cycling interval efficiency	PERcyc	%	-
Heating water operating limit temperature	WTOL	°C	57
Power consumption in modes other than active mode			
Off mode	P _{OFF}	kW	0,026
Thermostat-off mode	P _{TO}	kW	0,000
In standby mode	P _{SB}	kW	0,026
Crankcase heater mode	P _{CK}	kW	0,053
Supplementary heater			
Rated heat output supplementary heater	P _{sup}	kW	0,0
Type of energy input			Electric
Other items			
Capacity control			variable
Emissions of nitrogen oxides (only gas- or oil fired)	NO _x	mg/kWh	-
For air-to-water heat pumps: Rated air flow rate, outdoors		m ³ /h	7200
For brine-to-water heat pumps: Rated brine flow rate, outdoor heat exchanger		m ³ /h	-

Further important information for installation, maintenance as well as recycling and/or disposal are provided within the installation and operating manuals. Read and follow the installation and operating manuals.